

# Mychef Bakershop 4 600x400



### **TECHNICAL SPECIFICATIONS**

Capacity Distance between guides Rations per day Maximum temperature Dimensions (WxDxH) Weight Packaging dimensions (WxDxH) Gross weight Power Voltage

400/3L+N/50-60 R 3/4" Drainage No drainage 150 - 400 kPa Water pressure

4 x 600x400

760x760x522

900x830x1070

75 mm

58 Kg

74 Kg

6.3 kW

120-360 260 °C

## **GENERAL SPECIFICATIONS**

LCD control panel

Regulation of humidity, temperature, time and speed

40 programs with 3 cooking phases each

8 quick access memories

Convection cooking with humidity contribution from 30°C to

High thermal inertia camera

Fan stop when door is opened

Two fan speeds and reverse rotation

LED camera illumination

Low emission double glass hinged door

Door opening positioner

**EN Guides** 

Door and frame rainwater collection system with drainage

# **OPTIONALS**

Water

Door opening on the left hand side Water connection kit to carafe Connection 230V/L+N/50-60 Connection 230V/3L/50-60

# **ACCESSORIES**

Special trays for each baking

Washing shower

Condensation hood

**Detergent DA21** 

Support table

Wall bracket


WiFi connection

MyCloud remote control


Compatible with Google Home Voice Control




#### **INSTALLATION DETAILS**









## **SAFETY DISTANCES**


Sides = 50 mm

Rear = 100 mm

Upper = 500 mm


Heat sources = 1000 mm

It must be completely level



# **POWER CONNECTION**

|                          | Power (kW) | Current (A) |
|--------------------------|------------|-------------|
| 400/3L+N/50-60           | 6,3        | 14,2        |
| 230/L+N/50-60 (optional) | 6,3        | 27,4        |



# **WATER CONNECTION**

A Connection 3/4" treated water



Temperature < 30°C
Pressure 150 to 400 kPa dynamic flow
Hardness between 3° and 6° FH
PH between 6.5 and 8.5
Chlorides below 30 ppm
Use of water softener and filter required

