



Client \_\_\_\_\_ Quantity \_\_\_\_\_  
 Project \_\_\_\_\_ Position \_\_\_\_\_

## Vision Industry W150K F

**Model:** W150KFR-2D

**Cod:** W81320212001

### Technical data

<b>Max capacity:</b>	3 trolleys GN2/1, EN60x80
<b>Temperature range:</b>	-40°+65°C
<b>Ventilation range:</b>	25% - 100%
<b>Humidity range:</b>	45% - 95% with humidifier
<b>Humidifier:</b>	Incluso
<b>Refrigerant unit:</b>	Remote
<b>Yield +90 / +3:</b>	480 Kg
<b>Yield +90 / -18:</b>	360 Kg
<b>Cooling gas:</b>	R404/R452
<b>Defrost:</b>	Forced air
<b>Valve:</b>	Electronic expansion valve
<b>Dimensions:</b>	1600×3640×2510 mm
<b>Packing dimensions:</b>	N°3× 2755×1730×1690 mm
<b>Gross weight:</b>	1.250 Kg
<b>Voltage:</b>	400-415 V - 50-60 Hz
<b>Total rate:</b>	10810 W
<b>Absorbed Current:</b>	39,79 A

### Features

<b>Functions:</b>	Blast chilling, shock freezing, thawing, proving and retarder prover, holding, steam sanitizing, manualcycle
<b>Control:</b>	7" touch screen display with USB port
<b>Doors:</b>	Dictator closure to absorb sudden changes in pressure when opening and closing doors
<b>Door gasket:</b>	Magnetic, triple chamber and easily replaceable
<b>Core probe:</b>	Needle probe with 1 reading point, quick-release and easily replaceable
<b>Insulation:</b>	100 mm thickness - CFC/HCFC free
<b>Exterior/interior finishing:</b>	Internal and external in "linen canvas" steel
<b>Inner corners:</b>	Rounded base 20 mm
<b>Handle:</b>	In AISI 304 stainless steel
<b>Cosmo:</b>	Wi-Fi remote control system

### Remote unit technical data

<b>Voltage:</b>	400-415 V 3N - 50 Hz
<b>Cooling gas:</b>	R404-R452a
<b>HP unit:</b>	23
<b>Gross weight:</b>	521 Kg
<b>Dimensions:</b>	2180×1170×1208 mm
<b>Cooling capacity:</b>	Evap. -10°C Cond. +45°C

## Accessories and variants

Pavimento h 20 mm, rampa di accesso inclusa

Reverse door opening from standard

Door opening turning and control panel inversion

Door stop 100°

Sonda al cuore 3 punti di lettura

Sonda al cuore riscaldata 1 punto di lettura

Winter kit -20°C

Winter kit -40°C

Other special voltage

Offene Verflüssigungssätze 4GE-23Y W101K-W150K

Verflüssigungssätze mit Wetterschutzgehäuse 4GE-23Y für W101K-W150K

Unità condensante 4GE-23Y abb. W101K-W150K carenata cond. remoto

PVC ventilation profiles W150K

Ramp 100 mm high. Length 913 mm W40

Ramp 140 mm high. Length 1390 mm W40

Trolley GN1/1 20 trays 598x530x1630 mm

Trolley EN60x40 20 trays 460x620x1750 mm

Trolley GN2/1 20 trays 660x720x1750 mm

Trolley EN60x80 20 trays 660x820x1750 mm

Purity C Quell ST 50 filter cartridge


Sanitizing detergent

### COSMO - wi-fi control

Cosmo is the wi-fi technology that allow to connect, update and monitor with a smartphone the VISION blast chiller. VISION is also a Cosmo hub and allow remote supervision of the Coldline devices connected to it. From the app you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

\*The installation requires a kit for the replacement of the racks

## Technical draw



**A:** Power supply cable outlet

**B:** Condensation water drain

**C:** Floor grid for condensate drainage (recommended)

**I:** Internal led lighting

**L:** Door clear opening dimension

**N:** PVC ventilation profiles

**R:** Gas output pipes

**W:** Water mains connection for humidifier - 3/4" female. Unloading not required

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.