



Client _____ Quantity _____
 Project _____ Position _____

Vision Industry W200K F

Model: W200KFR-2D

Cod: W81420212001

Technical data

| | |
|----------------------------|----------------------------|
| Max capacity: | 4 trolleys GN2/1, EN60x80 |
| Temperature range: | -40°+65°C |
| Ventilation range: | 25% - 100% |
| Humidity range: | 45% - 95% with humidifier |
| Humidifier: | Incluso |
| Refrigerant unit: | Remote |
| Yield +90 / +3: | 640 Kg |
| Yield +90 / -18: | 480 Kg |
| Cooling gas: | R404/R452 |
| Defrost: | Forced air |
| Valve: | Electronic expansion valve |
| Dimensions: | 1600×4680×2510 mm |
| Packing dimensions: | N°3× 2755×1730×2000 mm |
| Gross weight: | 1.650 Kg |
| Voltage: | 400-415 V - 50-60 Hz |
| Total rate: | 14080 W |
| Absorbed Current: | 51,62 A |

Features

| | |
|-------------------------------------|--|
| Functions: | Blast chilling, shock freezing, thawing, proving and retarder prover, holding, steam sanitizing, manualcycle |
| Control: | 7" touch screen display with USB port |
| Doors: | Dictator closure to absorb sudden changes in pressure when opening and closing doors |
| Door gasket: | Magnetic, triple chamber and easily replaceable |
| Core probe: | Needle probe with 1 reading point, quick-release and easily replaceable |
| Insulation: | 100 mm thickness - CFC/HCFC free |
| Exterior/interior finishing: | Internal and external in "linen canvas" steel |
| Inner corners: | Rounded base 20 mm |
| Handle: | In AISI 304 stainless steel |
| Cosmo: | Wi-Fi remote control system |

Remote unit technical data

| | |
|--------------------------|-------------------------|
| Voltage: | 400-415 V 3N - 50 Hz |
| Cooling gas: | R404-R452a |
| HP unit: | 18 |
| Gross weight: | 418 Kg |
| Dimensions: | 1650×1050×876 mm |
| Cooling capacity: | Evap. -10°C Cond. +45°C |

Accessories and variants

Reverse door opening from standard
 Door opening turning and control panel inversion
 Door stop 100°
 Sonda al cuore 3 punti di lettura
 Sonda al cuore riscaldata 1 punto di lettura
 Winter kit -20°C
 Winter kit -40°C
 Other special voltage
 Unità condensante 4HE-18Y abb.W100K aperta
 Unità condensante 4HE-18Y abb. W100K carenata sil.
 Unità condensante 4HE-18Y abb. W100K carenata cond. remoto
 PVC ventilation profiles W200K
 Ramp 100 mm high. Length 913 mm W40
 Ramp 140 mm high. Length 1390 mm W40
 Trolley GN1/1 20 trays 598x530x1630 mm
 Trolley EN60x40 20 trays 460x620x1750 mm
 Trolley GN2/1 20 trays 660x720x1750 mm
 Trolley EN60x80 20 trays 660x820x1750 mm


Purity C Quell ST 50 filter cartridge
 Sanitizing detergent

COSMO - wi-fi control

Cosmo is the wi-fi technology that allow to connect, update and monitor with a smartphone the VISION blast chiller. VISION is also a Cosmo hub and allow remote supervision of the Coldline devices connected to it. From the app you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

*The installation requires a kit for the replacement of the racks

Technical draw



- | | | |
|-------------------------------------|---|--|
| A: Power supply cable outlet | B: Condensation water drain | C: Floor grid for condensate drainage (recommended) |
| I: Internal led lighting | L: Door clear opening dimension | N: PVC ventilation profiles |
| R: Gas output pipes | W: Water mains connection for humidifier - 3/4" female. Unloading not required | |

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.