



Client \_\_\_\_\_ Quantity \_\_\_\_\_  
 Project \_\_\_\_\_ Position \_\_\_\_\_

## Vision Industry W250LK U

**Model:** W250LKUR-2D

**Cod:** W80520212001

### Technical data

<b>Max capacity:</b>	5 trolleys 100x100
<b>Temperature range:</b>	-40°+10°C
<b>Ventilation range:</b>	25% - 100%
<b>Humidifier:</b>	Non disponibile
<b>Refrigerant unit:</b>	Remote
<b>Yield +90 / +3:</b>	1000 Kg
<b>Yield +90 / -18:</b>	800 Kg
<b>Cooling gas:</b>	R404/R452
<b>Defrost:</b>	Forced air
<b>Valve:</b>	Electronic expansion valve
<b>Dimensions:</b>	1850x5720x2510 mm
<b>Packing dimensions:</b>	N°4x 2755x1980x2000 mm
<b>Gross weight:</b>	2.130 Kg
<b>Voltage:</b>	400-415 V - 50-60 Hz
<b>Total rate:</b>	10675 W
<b>Absorbed Current:</b>	21,6 A
<b>Cooling capacity:</b>	114900 W*

### Features

<b>Functions:</b>	Blast chilling, shock freezing, continuous cycle
<b>Control:</b>	7" touch screen display with USB port
<b>Doors:</b>	Dictator closure to absorb sudden changes in pressure when opening and closing doors
<b>Door gasket:</b>	Magnetic, triple chamber and easily replaceable
<b>Core probe:</b>	Needle probe with 1 reading point, quick-release and easily replaceable
<b>Insulation:</b>	100 mm thickness - CFC/HCFC free
<b>Exterior/interior finishing:</b>	Internal and external in "linen canvas" steel
<b>Inner corners:</b>	Rounded base 20 mm
<b>Handle:</b>	In AISI 304 stainless steel
<b>Cosmo:</b>	Wi-Fi remote control system

### Remote unit technical data

<b>Voltage:</b>	400-415 V 3N - 50 Hz
<b>Cooling gas:</b>	R404-R452a
<b>HP unit:</b>	28
<b>Gross weight:</b>	1045 Kg
<b>Dimensions:</b>	2200x1300x1800 mm
<b>Cooling capacity:</b>	Evap. -10°C Cond. +45°C

## Accessories and variants

Reverse door opening from standard

Door opening turning and control panel inversion

Door stop 100°

Sonda al cuore 3 punti di lettura

Sonda al cuore riscaldata 1 punto di lettura

Winter kit -20°C

Winter kit -40°C

Predisposition for connection to CO2 remote control unit

Other special voltage

Unità condensante 6FE-44Y abb. W152K-W150LK carenata sil.

Unità condensante 4FE-28Y abb. W102K-W100LK carenata sil.

Unità condensante 6FE-44Y abb. W152K-W150LK carenata cond. remoto

Unità condensante 4FE-28Y abb. W102K-W100LK carenata cond. remoto

PVC ventilation profiles W250LK

Ramp 100 mm high. Length 913 mm W50L

Ramp 140 mm high. Length 1390 mm W50L

Trolley GN1/1 20 trays 598x530x1630 mm

Trolley EN60x40 20 trays 460x620x1750 mm

Trolley GN2/1 20 trays 660x720x1750 mm

Trolley EN60x80 20 trays 660x820x1750 mm

Purity C Quell ST 50 filter cartridge

Sanitizing detergent


Sterilizing UV lamp (U version)

### COSMO - wi-fi control

Cosmo is the wi-fi technology that allow to connect, update and monitor with a smartphone the VISION blast chiller. VISION is also a Cosmo hub and allow remote supervision of the Coldline devices connected to it. From the app you can check the operating conditions of each machine and receive alerts in the event of abnormal operation.

\*The installation requires a kit for the replacement of the racks

## Technical draw



**A:** Power supply cable outlet

**B:** Condensation water drain

**C:** Floor grid for condensate drainage (recommended)

**I:** Internal led lighting

**L:** Door clear opening dimension

**N:** PVC ventilation profiles

**R:** Gas output pipes

**W:** Water mains connection for humidifier - 3/4" female. Unloading not required

In order to constantly offer the best possible products we reserve the right to make changes on technical specifications without incurring any obligation for equipment previously or subsequently sold.